


Type	Ag* Al*	V <sub>DRM</sub> / V <sub>RRM</sub>	V <sub>DSM</sub> / V <sub>RSM</sub> [V]	I <sub>T(AV)</sub> [A]	Chip Size [mm] x [mm]	Package Options
CWP 39-22	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	2200	2300	72	10.00 10.0	sawn on foil <input checked="" type="checkbox"/> unsawn wafer <input checked="" type="checkbox"/> * in waffle pack <input checked="" type="checkbox"/>

\*Frontside options

\*Please contact IXYS chip sales



## Mechanical Parameters

Area active	0.48	cm <sup>2</sup>
Area total	1.00	cm <sup>2</sup>
Wafer size Ø	150	mm
Thickness	460	µm
Material	Si	
Max. possible chips per wafer	141	
Passivation front side	Glassivation	
Metallization top side	solderable: Ti / Ni / Ag *	
top side	bondable: Al	
Recom. wire bonds (Al)	Cathode	Gate
* = <i>Stitchbonds</i> Number / Ø [µm]	12* / 500	1 / 500
Metallization backside	solderable (only): Ti / Ni / Ag *	
Reject Ink Dot Size	Ø 0.4-1.0	mm
Recom. Storage Environment		
sawn on foil	in org. container, in dry nitrogen	< 6 month
unsawn wafer	in org. container, in dry nitrogen	< 2 year
in waffle pack	in org. container, in dry nitrogen	< 2 year
T <sub>stg</sub>	-40 ... 40	°C

### Features

- planar design (non-mesa)
- ultra rugged for easy assembly (flat backside)
- excellent long term stability
- very low leakage current
- very low forward voltage drop



### Applications

- DC motor control
- AC power control
- Softstart AC motor controller
- Light, heat and temperature control
- Solid state relays
- Controlled rectifier circuits

\*Sinterable top/bottom side on request

## Dimensions

A	B	C	D	E	H	J	K	L
[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
10.00	10.00	7.29	7.29	0.85	1.50	0.30	0.30	1.50



## Electrical parameters

Symbol	Conditions	Ratings		
		min.	typ.	max.
$I_R$	$V_D = V_r = V_{rr}$ $T_{VJ} = 25^\circ\text{C}$			0.5 mA
	$V_d = V_r = 1250\text{V}$ $T_{VJ} = 150^\circ\text{C}$			10 mA
$V_T$	$I_T = 100\text{ A}$ $T_{VJ} = 25^\circ\text{C}$			1.36 V
	$T_{VJ} = 150^\circ\text{C}$			1.42 V
$V_{T0}$	For power-loss calculations only			0.85 V
$r_T$	$T_{VJ} = 150^\circ\text{C}$			5.00 mΩ
$V_{GT}$	$V_D = 6\text{ V}$ $T_{VJ} = 25^\circ\text{C}$			1.5 V
	$T_{VJ} = -40^\circ\text{C}$			1.6 V
$I_{GT}$	$V_D = 6\text{ V}$ $T_{VJ} = 25^\circ\text{C}$			70 mA
	$T_{VJ} = -40^\circ\text{C}$			140 mA
$V_{GD}$	$T_{VJ} = 150^\circ\text{C}$ $V = \frac{2}{3} V_{DRM}$			0.2 V
$I_{GD}$				5 mA
$I_L$	$t_p = 10\ \mu\text{s}$ $T_{VJ} = 25^\circ\text{C}$ $I_G = 0.45\text{ A}$ $di_G/dt = 0.45\text{ A}/\mu\text{s}$			tbd mA
$I_H$	$R_{GK} = \infty$ $T_{VJ} = 25^\circ\text{C}$ $V_D = 6\text{ V}$			100 mA
$t_{gd}$	$V_D = \frac{1}{2} V_{DRM}$ $T_{VJ} = 25^\circ\text{C}$ $I_G = 0.5\text{ A}$ $di_G/dt = 0.5\text{ A}/\mu$			2 μs
$t_q$	$V_R = 100\text{ V}$ $I_T = 114\text{ A}$ $-di/dt = 10\text{ A}/\mu\text{s}$ $t_p = 200\ \mu\text{s}$ $dv/dt = 20\text{ V}/\mu\text{s}$ $V_D = \frac{2}{3} V_{DRM}$ $T_{VJ} = 125^\circ\text{C}$			150 μs
$(di/dt)_{cr}$	repetitive $I_T = 150\text{ A}$			150 A/μs
	non repetitive $I_T = 72\text{ A}$			500 A/μs
	$V = \frac{2}{3} V_{DRM}$ $T_{VJ} = 150^\circ\text{C}$ $di_G/dt = 0.45\text{ A}/\mu\text{s}$			
	$I_G = 0.45\text{ A}$ $t_p = 200\ \mu\text{s}$ $f = 50\text{ Hz}$			
$(dv/dt)_{cr}$	$T_{VJ} = 150^\circ\text{C}$ $V_{DR} = \frac{2}{3} V_{DRM}$ $R_{GK} = \infty$ method 1 (linear voltage rise)			1000 V/μs
$P_{GM}$	$T_{VJ} = 150^\circ\text{C}$ $t_p = 30\ \mu\text{s}$			10 W
	$t_p = 3E\ \mu\text{s}$			5 W
$P_{GAV}$				0.5 W
$V_{RGM}$				10 V
$T_{VJ}$		-40		150 °C
$I_{T(AV)}$	$T_C = 100^\circ\text{C}$ 180° rect.			72 A
	$T_{VJ} = 150^\circ\text{C}$ 180° sine			66 A
$I_{TSM}^*$	$T_{VJ} = 45^\circ\text{C}$ $t = 10\text{ ms}$ (50) Hz, sine			1000 A
	$V_R = 0\text{ V}$ $t = 8.3\text{ ms}$ (60) Hz, sine			1090 A
	$T_{VJ} = 150^\circ\text{C}$ $t = 10\text{ ms}$ (50) Hz, sine			tbd A
	$V_R = 0\text{ V}$ $t = 8.3\text{ ms}$ (60) Hz, sine			tbd A
$I^2t^*$	$T_{VJ} = 45^\circ\text{C}$ $t = 10\text{ ms}$ (50) Hz, sine			5000 A s <sup>2</sup>
	$V_R = 0\text{ V}$ $t = 8.3\text{ ms}$ (60) Hz, sine			4931 A s <sup>2</sup>
	$T_{VJ} = 150^\circ\text{C}$ $t = 10\text{ ms}$ (50) Hz, sine			tbd A s <sup>2</sup>
	$V_R = 0\text{ V}$ $t = 8.3\text{ ms}$ (60) Hz, sine			tbd A s <sup>2</sup>
$R_{thJC}^*$	DC current		tbd	K/W

\* Data according to assembled product tbd

Data according to IEC 60747

### Terms of Conditions and Usage

The data contained in this product data sheet is exclusively intended for technically trained staff. The user will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to his application. The specifications of our components may not be considered as an assurance of component characteristics. Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you. Due to technical requirements our product may contain dangerous substances. For any information on the types in question please contact the sales office/partner, which is responsible for you.

Should you intend to use the product in aviation applications, in health or life endangering or life support applications, please notify. For any such applications we urgently recommend

- to perform joint risk and quality assessments;
- the conclusion of quality agreements;
- to establish joint measures to ensure application specific product capabilities and notify that IXYS may delivery dependent on the realization of any such measures.